









PFR_M/APF_M SPECIFICATIONS Free Standing Type (Commercial)







MODE	L		Fancoil unit Condensing unit	PFR36M APF36M	PFR36MT APF36MT	PFR40M APF40M	PFR40MT APF40MT
Cooling capacity TIS. EGAT.		TIS.	Watt	10,600	10,600	11,800	11,800
		EGAT.	Btu/hr	36,100	36,100	40,944	40,944
Electri	Electrical Power		Watt	3,081.39	3,081.39	3,430.23	3,430.23
			Watt	3,070	3,070	3,330	3,330
COP	COP TIS		Watt/Watt	3.44	3.43	3.44	3.43
SEER	SEER		(Btu/hr)/W	13.33	13.33	13.11	13.33
	Power supply		V / Ph / Hz	220/1/50			
	Fan motor		Quantity	1	1	1	1
			RLA	1.94	1.94	1.94	1.94
FANCOIL UNIT			Air Direction	Left-Right Auto Swing, Up-Down Manual Swing			
NCC	Dimension	Width	m.m.	856	856	856	856
₹		Depth	m.m.	346	346	346	346
		Height	m.m.	1,889	1,889	1,889	1,889
			Kg.	90	90	90	90
E	Liquid		Inch	1/2	1/2	1/2	1/2
lect	Suction		Inch	3/4	3/4	3/4	3/4
Connection	Drain		Inch	3/4	3/4	3/4	3/4
	Power supply		V / Ph / Hz	220/1/50	380/1/50	220/1/50	380/1/50
	Compressor		Туре		Scroll		
_			RLA	14.50	5.30	16.70	5.70
I E	Fan motor		Quantity	1,	1	2	2
ENSING UNIT			RLA	0.85	0.85	0.85	0.85
ISI			Туре	R410A			
CONDE			Charging(g)	3,500	3,500	4,000	4,000
8	Dimension	Width	m.m.	968	968	968	968
		Depth	m.m.	356	356	356	356
		Height	m.m.	794	794	1,151	1,151
)	N.W.	Kg.	71	71	82	82

SIMILAR CO.,LTD.

235 Lasalle Road (Sukhumvit 105), Bangna, Bangna, Bangkok 10260 Thailand.

: marketing@eminent.co.th: www.eminent.co.th

: EminentAir



Distributed by:

* Aug 2017