





FREE STANDING TYPE
DECORATIVE



## PG\_M/AR\_M SPECIFICATIONS Free Standing Type (Decorative)







| Model   |                                  | Fancoil unit<br>Condensing unit                             | PG36M<br>AR36M  | PG36MT<br>AR36MT  | PG38M<br>AR38M   | PG38MT<br>AR38MT   |  |
|---|----------------------------------|---|---|---|--|--|--|
| Cooling capacity  Current  Power  EER  COP                          | TIS.<br>TIS.<br>TIS.             | Watt<br>Btu/hr<br>Amp<br>Watt<br>(Btu/hr)/W<br>Watt/Watt    | 10,600<br>36,167.2<br>16.50<br>3,533<br>10.24<br>3        | 10,600<br>36,167.2<br>5.40<br>3,533<br>10.24<br>3         | 11,200<br>38,214.4<br>17.50<br>3,733<br>10.24<br>3       | 11,200<br>38,214.4<br>5.70<br>3,733<br>10.24<br>3        |  |
| Power supply  |                                  | V-Ph-Hz   | 220-1-50  | 380-3-50  | 220-1-50   | 380-3-50   |  |
| Blower<br>Fan motor<br>Liquid<br>Suction<br>Drain<br>Unit Dimension | Width<br>Depth<br>Height<br>N.W. | Q'ty<br>Q'ty<br>Inch<br>Inch<br>Inch<br>m.m.<br>m.m.<br>Kg. | 1<br>1<br>1/2<br>3/4<br>3/4<br>600<br>380<br>1,940<br>53  | 1<br>1/2<br>3/4<br>3/4<br>600<br>380<br>1,940<br>53       | 1<br>1<br>1/2<br>3/4<br>3/4<br>600<br>380<br>1,940<br>53 | 1<br>1<br>1/2<br>3/4<br>3/4<br>600<br>380<br>1,940<br>53 |  |
| Refrigerant   |                                  | Туре  | R410A   |   |  |  |  |
| Fan blade Fan motor Compressor Liquid Suction Unit Dimension        | Width<br>Depth<br>Height<br>N.W. | Q'ty<br>Q'ty<br>Type<br>Inch<br>Inch<br>m.m.<br>m.m.<br>Kg. | 1<br>1<br>Scroll<br>1/2<br>3/4<br>968<br>308<br>794<br>71 | 1<br>1<br>Scroll<br>1/2<br>3/4<br>968<br>308<br>794<br>71 | 1<br>1<br>Scroll<br>1/2<br>3/4<br>968<br>356<br>794      | 1<br>1<br>Scroll<br>1/2<br>3/4<br>968<br>356<br>794      |  |

| Model   |                                  | Fancoil unit<br>Condensing unit                             | PG40M<br>AR40M  | PG40MT<br>AR40MT  | PG44MT<br>AR44MT  | PG48MT<br>AR48MT  | PG60MT<br>AR60MT  |
|---|----------------------------------|---|---|---|---|---|---|
| Cooling capacity  Current  Power  EER  COP                                  | TIS.<br>TIS.<br>TIS.             | Watt<br>Btu/hr<br>Amp<br>Watt<br>(Btu/hr)/W<br>Watt/Watt    | 11,800<br>40,261.6<br>18.40<br>3,933<br>10.24               | 11,800<br>40,261.6<br>6.10<br>3,933<br>10.24<br>3           | 13,000<br>44,356<br>7.60<br>4,333<br>10.24<br>3             | 14,100<br>48,109.2<br>8.2<br>4,700<br>10.24<br>3            | 17,600<br>60,051.2<br>10.30<br>5,867<br>10.24<br>3          |
| Power supply  |                                  | V-Ph-Hz   | 220-1-50  | 380-3-50  | 380-3-50  | 380-3-50  | 380-3-50  |
| Blower<br>Fan motor<br>Liquid<br>Suction<br>Drain<br>Unit Dimension         | Width<br>Depth<br>Height<br>N.W. | Q'ty<br>Q'ty<br>Inch<br>Inch<br>Inch<br>m.m.<br>m.m.<br>Kg. | 1<br>1/2<br>3/4<br>3/4<br>600<br>380<br>1,940               | 1<br>1<br>1/2<br>3/4<br>3/4<br>600<br>380<br>1,940<br>59    | 1<br>1/2<br>3/4<br>3/4<br>600<br>380<br>1,940<br>59         | 1<br>1/2<br>3/4<br>3/4<br>600<br>380<br>1,940<br>59         | 1<br>1<br>1/2<br>3/4<br>3/4<br>600<br>380<br>1,940<br>59    |
| Refrigerant   | Type R410A                       |   |   |   |   |   |   |
| Fan blade<br>Fan motor<br>Compressor<br>Liquid<br>Suction<br>Unit Dimension | Width<br>Depth<br>Height<br>N.W. | Q'ty<br>Q'ty<br>Type<br>Inch<br>Inch<br>m.m.<br>m.m.<br>Kg. | 2<br>2<br>Scroll<br>1/2<br>3/4<br>968<br>356<br>1,151<br>82 | 2<br>2<br>Scroll<br>1/2<br>3/4<br>968<br>356<br>1,151<br>82 | 2<br>2<br>Scroll<br>1/2<br>3/4<br>968<br>356<br>1,151<br>84 | 2<br>2<br>Scroll<br>1/2<br>3/4<br>968<br>356<br>1,151<br>84 | 2<br>2<br>Scroll<br>1/2<br>3/4<br>968<br>356<br>1,151<br>84 |

## SIMILAR CO.,LTD.

235 Lasalle Road (Sukhumvit 105),Bangna, Bangna, Bangkok 10260 Thailand.

: www.eminent.co.th: EminentAir



Distributed by:

\* Aug 2017