



turn to the experts™ 



38LB Series

Air Cooled Condensing Unit

48,000-150,000 BTUH

TT Air Engineering



โทร. 2134-2545



World's No.1 Air Conditioning Expert

www.carrier.co.th

www.ttair.co.th | Tel : 02-385-0728 | E-mail : sales@ttair.co.th | LINE ID : @ttair

38LB Series



The Practical and Versatile 38LB Air Cooled Condensing Units

Carrier introduces yet another innovative range of air conditioners - the **38LB** condensing units.

A versatile, energy-efficient series that adds a new dimension to air conditioning. Elegant designed and offering cool, quiet comfort, it is ideal for your home or office. Choose from 8 sizes of cooling capacity, there's one for every room requirement.

Features

- **Flexible Air Discharge Configuration - vertically (STD.) or horizontally.**
- **Direct Driven Condenser Fan - ensures quiet, dependable operation.**
- **Fully Hermetic Scroll Compressor - high efficiency, high reliability.**
- **High & Low Pressure Switches - ensures compressor protection.**
- **Shut off Service Valve - servicable units.**

Physical Data

Description		Air Cooled Condensing Unit					
Base Unit 38LB		048SC	060SC	007SC	009SC	012SC	015SC
Nominal Capacity*	Btu/hr	48,000	60,000	78,000	98,000	120,000	150,000
	Kw	14.1	17.6	22.9	28.7	35.2	44.0
Operating Weight (APPROX)	kg.	97	100	193	209	240	360
Compressor		Fully Hermetic Scroll Compressor					
Refrigerant**		R-22					
Operating Charged	kg.	3.0	3.1	5.3	5.5	6.2	10.0
Condenser Fans		Profeller, Direct Drive					
Fan Motor	V/Ph/Hz	220/1/50					
Piping Connections	Liquid in.	3/8		1/2		5/8	
	Suction in.	7/8		1 1/8		1 3/8	
Dimension	Height mm.	690		845		1050	
	Width mm.	800		900		1040	
	Depth mm.	725		915		1080	

* RATING CONDITION: OUTDOOR AMBIENT TEMPERATURE 95 F, SATURATED SUCTION TEMPERATURE 45 F

** UNIT SUPPLIED FROM FACTORY ONLY 4.5 LB FOR PRE-CHARGED

Electrical Data

Unit Model	Nominal Voltage	Voltage Range		Compressor		Fan Motor	
		MIN	MAX	RLA	LRA	QTY	RLA(ea)
38LB048SC	380-3-50	342	415	7.1	61	1	1.27
38LB060SC	380-3-50	342	415	8.6	74	1	1.27
38LB007SC	380-3-50	342	415	10.5	101	1	1.75
38LB009SC	380-3-50	342	415	15.8	114	1	1.75
38LB012SC	380-3-50	342	415	17.7	125	1	5.1
38LB015SC	380-3-50	342	415	25.6	175	1	5.1

RLA : RATED LOAD AMPS.

LRA : LOCKED ROTOR AMPS.

Carrier reserves the right to make changes in specifications without prior notice.
บริษัท แคนเนชั่น จำกัด ขอสงวนสิทธิ์ที่จะเปลี่ยนแปลงรายละเอียดข้างต้น โดยไม่ต้องแจ้งให้ทราบล่วงหน้า

บริษัท แคนเนชั่น (ประเทศไทย) จำกัด
ชั้น 14-15 อาคารเนชั่น ทาวเวอร์
1858/63-74 ถ.บางนา-ตราด กม. 4.5
บางนา กรุงเทพฯ 10260
โทร. 0-2762-9222 แฟกซ์ 0-2751-4778

Carrier (Thailand) Ltd.
14-15th Fl., Nation Tower,
1858/63-74 Bangna-Trad Road Km. 4.5,
Bangna, Bangkok 10260 Thailand
Tel.: 0-2762-9222 Fax: 0-2751-4778



YOUR CARRIER MAN :