

Console



Air Engineering



HW-SA201ABK YR-HRS01

-  DC fan motor
-  Space saving
-  Air discharge through top and bottom
-  Quiet operation

Model/Indoor unit			AF052MBERA	AF072MBERA	AF092MBERA	AF122MBERA	AF162MBERA	AF182MBERA
Capacity	Cooling	kBtu/h	5.1	7.5	9.5	12.3	15.3	17
		kW	1.5	2.2	2.8	3.6	4.5	5
	Heating	Btu/h	5.8	8.5	10.9	13.6	17	18.5
		kW	1.7	2.6	3.2	4	5	5.5
Electrical Parameters	Power supply	Ph/V/Hz	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60
	Air flow (H)	m³/h	540/460/390/310/270	540/460/390/310/270	540/460/390/310/270	580/500/420/350/270	620/540/460/390/270	620/540/460/390/270
Performance	Sound pressure level(H/M/L)	dB(A)	45/42/38/33/30	45/42/38/33/30	45/42/38/33/30	47/44/40/36/30	48/45/42/38/30	48/45/42/38/30
	External dimensions(W/D/H)	mm	700/210/600	700/210/600	700/210/600	700/210/600	700/210/600	700/210/600
Installation	Shipping dimensions(W/D/H)	mm	783/303/695	783/303/695	783/303/695	783/303/695	783/303/695	783/303/695
	Net/Shipping weight	kg	15.2/18.7	15.2/18.7	15.2/18.7	15.2/18.7	15.2/18.7	15.2/18.7
	Refrigerant liquid pipe	mm	6.35	6.35	6.35	6.35	6.35	6.35
	Refrigerant gas pipe	mm	12.7	12.7	12.7	12.7	12.7	12.7
Controller	Wired (Optional)	/	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK
	Infrared(Optional)	/	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01

MRV/Indoor Unit