



ODYSSEY DIRECT DRIVE

Split System

60,000 BTU/H Light Commercial

TTK & TTH R32 Series 50 Hz

TRANE
TECHNOLOGIES



TT Air

Odyssey - Light Commercial Split System Air Conditioner

Trane brand new light commercial AHU with direct drive evaporator fan motor specially design for free blow or short duct application to meet market requirement with low noise and smooth operation.



Quality and Reliability

- All units are 100 percent run tested prior leaving the production line.
- Ease of service with access doors on condensing unit and AHU.
- External current overload for compressor with under/over voltage & phase protector.

TTH Direct Drive Air Handling Units

- Special design direct drive 3-speed motor.
- Excellent full drain pan.
- Discharge plenum for evenly distributed airflow (option)



Direct Drive Motor

TTK Condensing Units

Standard Features

- Powder paint finish.
- Refrigerant shut-off valve.
- High & Low pressure switches.



TTK Model

Trane Thermostat (Option)



Digital room thermostat with 3 speeds fan adjustment and ON/OFF switch. Temperature setting can be adjusted from 18-30 °C with 7- segment LED display and auto restart function.

Options for TTK

- Blue fin, copper fin or anti-corrosion coating coil.

Product Specifications

Model	Indoor Unit		TTH060QB
	Outdoor Unit		TTKE60UD
Performance Data	Cooling Capacity	Btu/h	60,000
	Airflow	CFM	2,000
Indoor Unit			
Electrical Data	Power Supply	V/ph/Hz	220-240/1/50
No. of Refrigerant Circuit			1
Fan	Type		Forward Curve Centrifugal Fan
	Qty		1
Fan Motor	Type		Permanent Split Capacitor - Direct Drive
	RLA x Qty		2.02
Pre-Filter	Type		1-in Thickness Washable Aluminium
Dimensions	H x W x D	mm	635 x 1,312 x 916
Weight	Uncrated (net)	kg	82
Refrigerant Pipe Size	Suction	in	1-1/8
	Liquid	in	3/8
Outdoor Unit			
Electrical Data	Power Supply	V/ph/Hz	380-415/3/50
No. of Refrigerant Circuit			1
Expansion Device	Type		Capillary tube
Compressor	Type		Hemetic Rotary
	RLA x Qty	A	9.2
Fan Motor	RLA x Qty	A	0.65x2
Dimensions	H x W x D	mm	1,325x940x370
Weight (Each)	Uncrated (net)	kg	99
Piping Connection Type			Shut-off Valve - Flare Connection
Refrigerant Pipe Size	Suction	in	3/4
	Liquid	in	3/8
Refrigerant			R-32 (Fully Charged)

NOTE 1. Rated capacity at ARI system rating conditions 80°FDB/67°FWB indoor and 95°FDB outdoor.
2. Outdoor unit's width and depth do not included the size of the mounting feet. For more detail, please see the drawing in installation manual.
3. Product design and specifications are subject to change without notice.



TTKE60UD



เทรน (ประเทศไทย)

เลขที่ 1126/2 ชั้น 30-31 อาคารวานิช 2 ถนนพหลโยธิน แขวงมักกะสัน เขตราชเทวี กรุงเทพฯ 10400

☎ 0-2761-1111

©2022 Trane. All Rights Reserved.

SSA5-SLB001 Direct DriveR32-EN Nov 03, 2022

